



All the patents are held accountable counterfeiting.

Features

Green Power



- Standard/Din Rail Mounting Dual Purpose
- Easy mounting (one-step installation)
- Comply with High Efficiency Power 80Plus Criterion
- 90% High Efficiency
- “ Output Voltage Monitor ” Display (Optional)
- Convection cooled high reliability
- 100% burn-in test
- 2 years warranty
- Output modify range: 3V~200VDC

DIMENSIONS:100(H)\*83(D)\*49(W)mm WEIGHTS: 365g

General specifications

INPUT

Input range 90~264/120~380VAC  
220~380VDC

Input frequency 47~63Hz

Inrush current (25°C) 20A/110VAC  
40A/220VAC

Power factor 95% Min.

OUTPUT

Hold-up time 13ms

Short protection Autorecovery

Over load protection Automatic power limited

10A Power Ready Relay (Optional)

Detail specifications

120 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) 1			Ripple & Noise 4	Line REG. 2	Load REG. 3	Efficiency 5	O.V.P
		Min.	Rated	Max.					
RPH1120D-12CTNDA	V : +12V ±10%	0A	10.0A	10.0A	120mV	±1%	±1%	89% Ref.	17.1 ~ 18.9V
RPH1120D-24CTNDA	V : +24V ±10%	0A	5.0A	5.0A	240mV	±1%	±1%	90% Ref.	31.4 ~ 34.7V
RPH1120D-48CTNDA	V : +48V ±10%	0A	2.5A	2.5A	480mV	±1%	±1%	91% Ref.	64.6 ~ 71.4V

Please Choose Fit Function,And Fill In The Blank With Suitable Words.

Order Model:RPH1120D-24C  N

Optional Function:

Terminal Block: "T" : PCB Barrier Terminal Block ←  
 "E" : Mini Terminal Block ←

Motion: " " : No Monitor ←  
 "D" : Monitor Display ←

Type: " " : No Display Function ←  
 "A" : Output Voltage Display ←

CE Standards

EN 61000-3-2, EN 61000-3-3  
 EN 61000-6-2, EN 61000-6-4,  
 (EN 61000-4-2, EN 61000-4-3,  
 EN 61000-4-4, EN 61000-4-5,  
 EN 61000-4-6, EN 61000-4-8,  
 EN 61000-4-11),  
 Heavy Industry level, criteria A

Safety Standards

UL 508 Meet

CE Marking

Environments

Operating Temperature -15 ~ 50°C, Ambient

Operating Humidity 20 ~ 90% RH, No Condensing

Storage Temperature -20 ~ 85°C, Ambient

Vibration 2G, 10~500Hz, 3 axes

NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output Voltage Adjustable is measured on 5% of rated load.
8. Reign Power reserve the right to change specifications at any time without notice.

WEB : <http://www.switching-powers.com>  
 E-mail : [rp21003f@ms7.hinet.net](mailto:rp21003f@ms7.hinet.net)

Tel : 886-2-22997550  
 Fax : 886-2-22997596

