



Features



DIMENSIONS: 100(H)*110(D)*60(W)mm
WEIGHTS: 500g

- Convection cooled
- **Din Rail/ Screw Mounting Dual Purpose**
- 100% burn-in test
- Easy mounting (one-step installation)
- Separation of AC and DC, Excellent of Anti-Electromagnetic interference
- RoHS & EMI test and strictness on quality
- 2 year Warranty
- **Split rail & Series connection possible**
- **Output modify range: 3V~200VDC**

General specifications

INPUT

Input range	90~132/180~264VAC (Selectable) 220~380VDC
Input frequency	47~63Hz
Inrush current (25° C)	20A/110VAC 40A/220VAC

OUTPUT

Hold-up time	16mS
Short protection	Autorecovery
Overload protection	Automatic power limited
Over voltage protection	Optional

Detail specifications

100 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V. P.
		Min.	Rated	Max.					
RP2100D1M	V1:+5V ±10% V2:+12V ----	0A 0A	3A 7.1A	3A 7.1A	60mVp-p 100mVp-p	±1% ±1%	±1% ±4%	72% Min.	5.8 ~ 7.0V -----
RP2100D2M	V1:+5.15V ±10% V2:+24V ----	0A 0A	3A 3.53A	3A 3.53A	60mVp-p 200mVp-p	±1% ±1%	±1% ±4%	75% Min.	5.8 ~ 7.0V -----
RP2100D3M	V1:+24V ±10% V2:-24V ----	0A 0A	2.1A 2.1A	2.1A 2.1A	200mVp-p 200mVp-p	±1% ±1%	±1% ±4%	77% Min.	27.6 ~ 31V -----

CE Standards

EN 55022 CLASS A,
EN 61000-3-2 CLASS A,
EN 61000-3-3, EN 55024,
(EN 61000-4-2, EN 61000-4-3,
EN 61000-4-4, EN 61000-4-5,
EN 61000-4-6, EN 61000-4-8,
EN 61000-4-11)

Safety Standards

	UL 60950 Meet
	CUL 60950 Meet
	CE Marking

Environments

Oper rating Temperature	-15 ~ 50°C, Ambient
Oper rating Humi dity	20 ~ 90% RH, No Condensing
Storage Temperature	-20 ~ 85°C, Ambient
Vibration	2G, 10~500Hz, 3 axes

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 220VAC input. (Redundant function Sepc. 0.6V Add.)
 4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
 5. Efficiency is measured at rated load and 220VAC input.
 6. Hold-up time is measured at rated load and 220VAC input.
 7. Output Voltage Adjustable is measured on 5% of rated load.
 8. Reign Power reserve the right to change specifications at any time without notice.

WEB : <http://www.switching-powers.com>
E-mail : rp21003f@ms7.hinet.net

Tel : 886-2-22997550
Fax : 886-2-22997596

REIGNPOWER
S.M.P.S