



All the patents are held accountable counterfeiting.

## Features



## Green Power

- Din Rail / Screw Mounting Dual Purpose
- Easy mounting (one-step installation)
- " Output Voltage Monitor " Display
- Fan speed control(PCB damp proof process)
- 100% burn-in test
- 1 years warranty
- Output modify range: 3V~200VDC

DIMENSIONS:100(H)\*110(D)\*60(W)mm

WEIGHTS: 550g

## General specifications

## INPUT

Input range	90~132/180~264VAC(Selectable) 220~380VDC
Input frequency	47~63Hz
Inrush current (25°C)	20A/110VAC 40A/220VAC

## OUTPUT

Hold-up time	10ms
Short protection	Autorecovery
Over load protection	Automatic power limited

## Detail specifications

## 350 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) <sup>1</sup>			Ripple & Noise <sup>4</sup>	Line REG. <sup>2</sup>	Load REG. <sup>3</sup>	Efficiency <sup>5</sup>	O.V.P
		Min.	Rated	Max.					
LP1350D-24M	V : +24V ±10%	0A	14.6A	14.6A	240mV	±1%	±2%	79% Ref.	31.4 ~ 34.7V

Please Choose Fit Function, And Fill In The Blank With Suitable Words.

Order Model: LP1350D-24M  

Optional Function:

Terminal Block: " " : PCB Barrier Terminal Block ← "E" : Mini Terminal Block ←  
 Motion: " " : No Monitor ← "D" : Monitor Display ←  
 Type: " " : No Display Function ← "A" : Output Voltage Display ←

## CE Standards

EN 55022 CLASS A,  
 EN 61000-3-3, (EN 61000-4-2,  
 EN 61000-4-3, EN 61000-4-4,  
 EN 61000-4-5, EN 61000-4-6,  
 EN 61000-4-8, EN 61000-4-11)

## Safety Standards

LISTED  
 IND. POINT. EQ.  
 520B E225775  
 UL 508 Meet  
 CE Marking

## Environments

Operating Temperature -15 ~ 50°C, Ambient  
 Operating Humidity 20 ~ 90% RH, No Condensing  
 Storage Temperature -20 ~ 85°C, Ambient  
 Vibration 2G, 10~500Hz, 3 axes

## NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output Voltage Adjustable is measured on 5% of rated load.
8. Reign Power reserve the right to change specifications at any time without notice.