


Overview

- M12, female, A-coded, 5-poles; PVC, 2500 cm, open cable end
- Head A: IP65, IP66K, IP67



Technical data

Side A

Head A: Connection	M12
Head A: Angle cable outlet	0°
Head A: Gender	Female
Head A: Coding	A
Head A: No. of poles	5
Head A: LED	No
Head A: Width across flats	AF13
Head A: Tightening torque	0.6 Nm
Head A: Knurled nut material	Zinc-pressure die casting, surface Ni
Head A: Body color	Black
Head A: Gasket material	FKM
Head A: Contact layout pin 1	BN
Head A: Contact layout pin 2	WH
Head A: Contact layout pin 3	BU
Head A: Contact layout pin 4	BK
Head A: Contact layout pin 5	GY

Side B

Head B: Connection	Open-ended wires
--------------------	------------------

Cables

Cable length	3000 cm
Stripping length	20 mm
Shielded	No
Conductor structure	19 × 0.15 mm
AWG	22
External sheath: Material	PVC
External sheath: Color	Gray
Cable diameter	5.2 mm ±5 %
Wire cross section	0.34 mm ²
Cable: Halogen free	No

Cable

Cable: Temperature range (mobile)	- 5 ...+ 80 °C
Cable: Temperature range (fixed)	- 30 ...+ 80 °C
Shielded	No
Bending radius (fixed)	26 mm
Number of wires	5
Number and diameter of wires	5x0.34
Cable length	3000 cm
AWG	22
Bending radius (fixed)	Min. 5 × outer diameter
Bending radius (mobile)	Min. 10 × outer diameter
Cable type	1
Conductor structure	19 × 0.15 mm
Cable diameter	5.2 mm ±5 %
Conductor: Material	Copper, bare
External sheath: Material	PVC
Insulation: Material	PVC
Paired stranding	No
Single wire diameter	0.15 mm
Cable: Test voltage	2 kV
Total stranding	5 wires strand around core-filler
Travel speed (C-track)	0
Wire cross section	0.34 mm ²
Wire processing	No
Wire diameter incl. isolation	1.25 mm ±5 %
External sheath: Color	Gray

Electrical data

Operating voltage	Max. 125 V AC/DC 0
Contact resistance	Max. 30 mOhm
Operating current per contact	Max. 4 A

Mechanical data

Bending radius (mobile)	Min. 10 × outer diameter
-------------------------	--------------------------

Technical data
Mechanical data

Bending radius (fixed)	Min. 5 × outer diameter
Travel speed (C-track)	0

Environmental conditions

Temperature range (mobile)	- 5 ...+ 80 °C
Temperature range (fixed)	- 25 ...+ 80 °C
Cable: Temperature range (fixed)	- 30 ...+ 80 °C
Dragchain capable	No
Head A: Chemical resistance	No
Head A: Flame resistance	HB (UL 94)

Environmental conditions

Head A: Oil resistance	Good resistance to ASTM 1 oil and mineral oils. Limited resistance to hydraulic oils. If other oils are used, the resistance must be checked in relation to the application.
Head A: Acid and alkali resistant	No
Head A: Pollution degree	3
Cable: Chemical resistance	Good
Cable: Flame resistance	Conform UL 1581 VW-1
Cable: Oil resistance	Good
Cable: Silicone-free	Yes