



## AC → DC SWITCHING POWER SUPPLY

## LP1500D SERIES

All the patents are held accountable counterfeiting.

### Features



### Green Power

- Din Rail / Screw Mounting Dual Purpose
- Easy mounting (one-step installation)
- Comply with High Efficiency Power 80Plus Criterion
- "Output Voltage Monitor" Display
- Fan speed control(PCB damp proof process)
- 100% burn-in test
- 1 years warranty
- Output modify range: 3V~200VDC

DIMENSIONS:100(H)\*110(D)\*90(W)mm

WEIGHTS: 820g

### General specifications

#### INPUT

Input range 90~132/180~264VAC(Selectable)  
220~380VDC

Input frequency 47~63Hz

Inrush current (25°C) 20A/110VAC  
40A/220VAC

#### OUTPUT

Hold-up time 13ms

Short protection Autorecovery

Over load protection Automatic power limited

### Detail specifications

#### 500 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) <sup>1</sup>			Ripple & Noise <sup>4</sup>	Line REG. <sup>2</sup>	Load REG. <sup>3</sup>	Efficiency <sup>5</sup>	O.V.P
		Min.	Rated	Max.					
LP1500D-12M	V : +12V ±10%	0A	37.5A	41.6A	180mV	±1%	±2%	85% Ref.	17.1 ~ 18.6V
LP1500D-24M	V : +24V ±10%	0A	20.8A	20.8A	240mV	±1%	±2%	85% Ref.	31.4 ~ 34.7V
LP1500D-48M	V : +48V ±10%	0A	10.4A	10.4A	480mV	±1%	±2%	85% Ref.	64.6 ~ 71.4V

Please Choose Fit Function, And Fill In The Blank With Suitable Words.

Order Model: LP1500D-24M ☐ ☐ ☐

Optional Function:

Terminal Block: " " : PCB Barrier Terminal Block

"E" : Mini Terminal Block

Motion: " " : No Monitor

"D" : Monitor Display

Type: " " : No Display Function

"A" : Output Voltage Display

### CE Standards

EN 55022 CLASS A,  
EN 61000-3-3, (EN 61000-4-2,  
EN 61000-4-3, EN 61000-4-4,  
EN 61000-4-5, EN 61000-4-6,  
EN 61000-4-8, EN 61000-4-11)

### Safety Standards



UL 508 Meet



CE Marking

### Environments

Operating Temperature

-15 ~ 50°C, Ambient

Operating Humidity

20 ~ 90% RH, No Condensing

Storage Temperature

-20 ~ 85°C, Ambient

Vibration

2G, 10~500Hz, 3 axes

### NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output Voltage Adjustable is measured on 5% of rated load.
8. Reign Power reserve the right to change specifications at any time without notice.

WEB : <http://www.switching-powers.com>

E-mail : [rp21003f@ms7.hinet.net](mailto:rp21003f@ms7.hinet.net)

Tel : 886-2-22997550

Fax : 886-2-22997596

**REIGNPOWER**  
S.M.P.S