



SLC240COM-ER-1050-35

- Safety type 2 in accordance with IEC 61496-1
- User-friendly parameter setting, no tools required
- Reliable safety concept in case of interferences (EMC, welding sparks)
- Process safety with highest availability
- active integrated set-up tool

Data

Ordering data

Product type description	SLC240COM-ER-1050-35
Article number (order number)	103016262
EAN (European Article Number)	4030661506869
eCl@ss number, Version 9.0	27-27-27-04
eCl@ss number, Version 11.0	27-27-27-04

Approval - Standards

Certificates	TÜV cULus
--------------	--------------

General data

Standards	EN 61496-1 EN 61496-2
Master- or Slave-function	Yes
Enclosure material	Aluminium
Gross weight	1,740 g
Reaction time, maximum	20 ms

General data - Features

Cascadable	Yes
Restart interlock (manual reset)	Yes
Hide function	Yes
Integral System Diagnostics, status	Yes
Integral System Diagnostics	Yes
Number of beams	36
Number of fail-safe digital outputs	2

Safety appraisal

Standards	EN ISO 13849-1 EN 62061
Performance level, up to	c
Control category to EN13849	2
PFH-value	8.05×10^{-9} /h
Safety Integrity Level (SIL), suitable for applications in	1
Mission Time	20 Year(s)
Safety type in accordance with IEC 61496-1	2

Mechanical data

Detection ability for test bodies at $v = 1.6$ m/s	35 mm
Height of the protection field	1,050 mm
Range, protection field, minimum	300 mm
Range, protection field, maximum	7,000 mm
Wave length of the sensor	880 nm

Mechanical data - Connection technique

Terminal Connector	Connector
Terminal connector, Recipient	Connector plug M12, 5-pole
Terminal, Connector, Transmitter	Connector plug M12, 4-pole
Length of the connectable cable, maximum	100 m

Mechanical data - Dimensions

Length of sensor	33 mm
Width of sensor	27.8 mm
Height of sensor	1,091 mm

Ambient conditions

Degree of protection	IP67 to EN 60529
Ambient temperature, minimum	-10 °C
Ambient temperature, maximum	+50 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Protection rating	III

Electrical data

Voltage type	DC (direct current)
Switching voltage OSSD, HIGH signal	24 V
Electrical power consumption of the receiver, maximum	10 W
Electrical power consumption of the transmitter, maximum	5 W

Electrical data - Fail-safe digital outputs

Output current, (fail-safe output), maximum	0.25 A
Versions	p-type

Scope of delivery

Included in delivery	Kit with 2 mounting angles
----------------------	----------------------------

Accessory

Recommended safety switchgear	SRB-E 301
-------------------------------	-----------

Ordering code

Product type description:
SLC240COM-ER(1)-(2)

(1)

0330	Protection field height 330 mm
0410	Protection field height 410 mm
0490	Protection field height 490 mm
0570	Protection field height 570 mm
0650	Protection field height 650 mm
0730	Protection field height 730 mm
0810	Protection field height 810 mm
0890	Protection field height 890 mm
0970	Protection field height 970 mm
1050	Protection field height 1050 mm
1130	Protection field height 1130 mm
1210	Protection field height 1210 mm
1290	Protection field height 1290 mm
1370	Protection field height 1370 mm
1450	Protection field height 1450 mm
1530	Protection field height 1530 mm
1610	Protection field height 1610 mm
1690	Protection field height 1690 mm
1770	Protection field height 1770 mm
1850	Protection field height 1850 mm
1930	Protection field height 1930 mm

(2)

14	Resolution 14 mm
30	Resolution 30 mm
35	Resolution 35 mm

Pictures

Product picture (catalogue individual photo)




ID: kslc4f67

| 1,005.9 kB | .jpg | 352.778 x 1212.144 mm - 1000 x 3436 px - 72 dpi

| 66.6 kB | .png | 74.083 x 254.353 mm - 210 x 721 px - 72 dpi

| 16.9 kB | .jpg | 79.728 x 273.756 mm - 226 x 776 px - 72 dpi

Dimensional drawing basic component




ID: 5slc4g23

| 76.2 kB | .ai | 210.002 x 297 mm - 595 x 841 px - 72 dpi

| 5.0 kB | .png | 74.083 x 158.75 mm - 210 x 450 px - 72 dpi

| 196.0 kB | .jpg | 352.778 x 757.061 mm - 1000 x 2146 px - 72 dpi

Wiring example



ID: kslc2l06

| 124.5 kB | .jpg | 352.778 x 475.544 mm - 1000 x 1348 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 20/08/2021, 13:37